

CARRILES TENSORES EN ACERO
STEEL MOTOR RAILS



Ref.	L	GI	H	Mxh	lxS	G2	a	b	b/2	od	B	HI	H2	Kg
312/6	312	240	63/71	M 6x19	72x6	262	16	280	-	12	40	28	30	1,4
312/8	312	240	80/90	M 8x27	75x6	262	16	280	-	12	40	28	30	1,5
375/6	375	305	63/71	M 6x19	75x6	325	16	343	-	12	40	28	30	1,5
375/8	375	305	80/90	M 8x27	75x6	325	16	343	-	12	40	28	30	1,6
375/10	395	305	100/112	M10x32	75x6	325	16	343	-	12	40	28	30	1,6
395/8	395	302	80/90	M 8x28	97x8	325	20	355	-	12	50	40	43	3,4
395/10	495	302	100/112	M 10x35	97x8	325	20	355	-	12	50	40	43	3,4
495/8	495	405	80/90	M 8x29	97x8	425	20	455	-	12	50	40	43	4
495/10	495	405	100/112/132	M 10x35	97x8	425	20	455	-	12	50	40	43	4
495/12	530	405	160	M 12x49	97x8	425	20	455	-	12	50	40	43	4
530/10	530	413	132	M 10x37	119x9	442	25	480	-	14	60	50	54	6,4
530/12	530	413	160	M 12x49	119x9	442	25	480	-	14	60	50	54	6,4
630/10	630	515	132	M 10x37	119x9	542	25	580	-	14	60	50	54	8,2
630/12	630	515	160/180	M 12x45	119x9	542	25	580	-	14	60	50	54	8,2
686/12	686	538	160/180	M 12x43	154x12	575	28	630	315	18	75	60	64	12,8
686/16	686	538	200/225	M 16x62	154x12	575	28	630	315	18	75	60	64	12,8
864/16	864	700	200/225	M 16x60	300x16	810	32	800	400	24	90	75	-	16,6
864/20	864	700	250/280	M 20x68	300x16	810	32	800	400	24	90	75	-	16,6
1072/20	1072	865	250/280	M 20x77	360x19	995	36	1000	500	30	112	100	-	33,4
1072/24	1072	865	315	M24x88	360x19	995	36	1000	500	30	112	100	-	33,5
1330/24	1330	1065	315/355	M 24x95	430x21	1215	40	1250	625	30	130	125	-	56,6

